

CEMENTING & ACIDIZING UNIT



Sanjel's Cementing & Acidizing (C&A) Unit provides three key benefits: Reliability, Simplicity, and Mobility. The unit's mixing system and hydraulics are powered by the independent Auxiliary Diesel Engine, leaving the entire 475 hp road engine available for downhole pumping. The C&A provides tremendous versatility in a compact package, able to mix and pump cements, diesel gel, diesel gel cement, batch frags, acid, acid solvents and sand slurries. The Cementing & Acidizing Unit is field-designed and fabricated to withstand extreme weather conditions.

Applications

- Shallow to deep well applications
- Critical and sour gas wells
- Surface, intermediate and production casings
- Liner cementing operations
- Injectivity tests
- Conductor barrels and well kills
- High pressure pumping operations
- Remedial cementing and acidizing operations

Equipment

- 125 hp auxiliary diesel engine
- 475 hp triplex pump
- 3" x 2" centrifugal mixing pump with 13" impeller
- 5" x 4" centrifugal pre-charge pump with 12" impeller
- 2 – 20 bbl sealed displacement/batch tanks with hydraulic augers
- 2" treating iron package
- Cementing hose reel with 75 ft of hose
- Blower for bin operations or bulk transport redundancy

Instrumentation and Control Systems

- Real-time Field Data Acquisition System (FDAS)
- Digital rate and total flow readouts
- Independent Martin Decker pressure gauge and chart recorder
- 10000 psi adjustable mechanical relief valve
- Transfer case safety protection mechanism for switching between road and pump gear

Performance

- Maximum Mixing Rate: 7.5 bbl/min
- Maximum Pumping Rate: 10 bbl/min with 5" plunger
- Maximum Cementing Pressure: 6000 psi
- Maximum Acidizing Pressure: 10000 psi with 3.5" plunger
- Batch Capacity: 40 bbl (1680 usg)